



**OPAL-RT
TECHNOLOGIES**



DECLARATION OF CONFORMITY

Manufacturer Name: OPAL-RT Technologies Inc.
Manufacturer Address: 1751 Richardson suite 2525, Montreal,
QC H3K 1G6 Canada
www.opal-rt.com

This declaration of conformity is issued under the sole responsibility of:

OPAL-RT Technologies Inc.

Product Model / Product:

OP5707XG or OP5707-IO with any of the following options
OP5330-3
OP5340
OP5342
OP5353
OP5360-3
OP5363
OP5367-1
OP5367-3
OP5367-5
OP5368
OP5369
OP3411 (CAN kit)
OP3811 / OP3812 (Oregano kit)
OP5455 (Copper PCIe kit)
PXH832 or T00-7284 (Dolphin optical PCIe kit)
I350T4V2BLK (Ethernet)

Product Description:

Simulator with Digital and Analog Input and Output cards intended for indoor use only.
Ratings: 230V, 4A, 50Hz, 600W max, pollution degree 2

Product category:

Electrical equipment for measurement, control, and laboratory use.

CE Conformity with the relevant Community harmonisation legislation:

2014/30/EU – Electromagnetic Compatibility Directive
2014/35/EU – Low Voltage Directive
2011/65/EU & (EU) 2015/863 – Restriction of Hazardous Substances in Electrical and Electronic Equipment (RoHS) directive
2012/19/EC – Waste from Electrical and Electronic Equipment (WEEE) Directive

UKCA Conformity with the relevant harmonisation legislation:

Electromagnetic Compatibility Regulations 2016
 Electrical Equipment (Safety) Regulations 2016
 The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic
 Equipment Regulations 2012

References to the standards in relation to which conformity is declared		
Category	Standards	Test Specifications
Emissions:	EN61326-1 (2013) / IEC61326 (2012)	
	EN55011 (2016) A1(2017) CISPR11(2015) A1(2016)	Conducted Emissions: Group 1 - class A 150kHz-30MHz Radiated Emissions: Group 1 - class A 30MHz-1GHz
Immunity:	EN61000-4-2 (2009) / IEC61000-4-2 (2008)	Contact: $\pm 4\text{kV}$ Air: $\pm 2\text{kV}$, $\pm 4\text{kV}$, $\pm 8\text{kV}$
	EN61000-4-3 (2006) A1(2007) A2 (2010) IEC61000-4-3 (2006) A1(2008) A2(2010)	80MHz-1000MHz: 10V/m 1.4GHz-2GHz: 3V/m 2GHz-2.7GHz: 1V/m
	EN61000-4-4 (2012) IEC61000-4-4 (2012)	Power: $\pm 2\text{kV}$ / 5kHz I/O Ports: N/A Communication Ports (Ethernet): $\pm 1\text{kV}$ / 5kHz
	EN61000-4-5 (2014) IEC61000-4-5 (2014)	Power: $\pm 2\text{kV}$ L-PE / $\pm 1\text{kV}$ L-L I/O Ports: N/A Communication Ports: N/A
	EN61000-4-6 (2014) / IEC61000-4-6 (2013)	Power: 3V I/O Ports: N/A Communication Ports (Ethernet): 3V
	EN61000-4-8 (2010) / IEC61000-4-8 (2009)	Continuous Field: 30A/m / 50Hz
	EN61000-4-11 (2004) A1 (2017) IEC61000-4-11 (2004) A1 (2017)	Voltage dips: 0%Un during half cycle 0%Un during 1 cycle 40%Un during 10 cycles (at 50Hz) 70%Un during 25 cycles (at 50Hz) Short interruptions: 0%Un during 250 cycles (at 50Hz)
Safety:	EN 61010-1 / IEC 61010 Edition 3.1 2017-01	



2022-10-25

Date: _____

Authorised representative
François Gagnon
Head of Division / Electronic
OPAL-RT TECHNOLOGIES