





DECLARATION OF CONFORMITY

Manufacturer Name: OPAL-RT Technologies Inc.

Manufacturer Address: 1751 Richardson suite 1060, Montreal,

QC H3K 1G6 Canada www.opal-rt.com

This declaration of conformity is issued under the sole responsibility of:

OPAL-RT Technologies Inc.

Product Model / Product:

OP5020XG with any of the following options		
OP3411 (CAN kit)		
OP5455 (Copper PCle kit)		
I350T4V2BLK (Ethernet)		

Product Description:

Simulator with Digital and Analog Input and Output cards intended for indoor use only. Ratings: 100-240 VAC, 400W max, pollution degree 2

Product category:

Electrical equipment for measurement, control, and laboratory use.

CE Conformity with the relevant Community harmonisation legislation:

2014/30/EU - Electromagnetic Compatibility Directive

2014/35/EU - Low Voltage Directive

2011/65/EU & (EU) 2015/863 - Restriction of Hazardous Substances (RoHS) in Electrical

and Electronic Equipment directive

2012/19/EU - Waste from Electrical and Electronic Equipment (WEEE) Directive

UKCA Conformity with the relevant harmonisation legislation:

Electromagnetic Compatibility Regulations 2016

Electrical Equipment (Safety) Regulations 2016

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic

Equipment Regulations 2012

Category	Standards	Test Specifications
Emissions:	EN IEC 61326-1:2021	
	EN55011 (2016) A1(2017) CISPR11(2015) A1(2016) A2 (2019)	Conducted Emissions: Group 1 - class A 150kHz-30MHz Radiated Emissions: Group 1 - class A 30MHz-20GHz
Immunity:	IEC61000-4-2 (2008)	Contact: ±4kV Air: ±2kV, ±4kV, ±8kV
	IEC61000-4-3 (2020)	80MHz-1000MHz: 10V/m 1.4GHz-6GHz: 3V/m
	IEC61000-4-4 (2012)	Power: ±2kV / 5kHz & 100kHz I/O Ports: N/A Communication Ports (Ethernet): ±1kV / 5kHz & 100kHz
	IEC61000-4-5 (2014) A1 (2017)	Power: ±2kV L-PE / ±1kV L-L I/O Ports: N/A Communication Ports: N/A
	IEC61000-4-6 (2013)	Power: 3V I/O Ports: N/A Communication Ports (Ethernet): 3V
	IEC61000-4-8 (2009)	Continuous Field: 30A/m – 50Hz & 60Hz
	IEC61000-4-11 (2020)	Voltage dips: 0%Un during 1 cycle 40%Un during 10 cycles (at 50Hz) 40%Un during 12 cycles (at 60Hz) 70%Un during 25 cycles (at 50Hz) 70%Un during 30 cycles (at 60Hz) Short interruptions:
		0%Un during 250 cycles (at 50Hz) 0%Un during 300 cycles (at 60Hz)
Safety:	EN 61010-1 :2010/A1 :2019 IEC 61010-1 :2010, IEC 61010-1 :2010/AMD1 :2016	

Authorised representative

Pascal Carrieres

Director - R&D Platform / Directeur(trice) - Plateforme R&D

OPAL-RT TECHNOLOGIES

Date: 2024-03-28